

TECHNICAL DATA SHEET

Name :	Nylon 70D/190T WR PVC REACH			
Supplier :	KINETIC s.r.o. SNP 9/6 ; 796 07 Držovice IČO:27728234 ; DIČ: CZ27728234 tel.: 582 365 770 email : kinetic@kinetic.cz			
Manufactured :	Taiwan			
Description :	Nylon 70D/190T WR PVC REACH			
Textile :	<u>100% NYLON</u>			
Lamination :	PVC			
Weight :	165 g/m2			+/- 5%
Dimensions :	fabric width 58" - length 1 roll 50m			
Tensile strength :	warp	1902		+/- 5%
(ISO 13934-1 (N))	weft	268		+/- 5%
Tear strength :	warp	71		+/- 5%
(ISO13937-2 (N))	weft	44		+/- 5%
Adhesion of coating to fabric	warp	30.83		+/- 5%
ASTM D751-19 (N)	weft	28.84		+/- 5%
Water column:				
AATCC-127 (mmH2O)		>2000		
Abrasive resistance				
ISO 12947-2 (Cycles)		25000		
Laundry symbols :	 DO NOT WASH, DO NOT BLEACH, DO NOT TUMBLE DRY, DO NOT IRON, DO NOT DRY CLEAN			
Suitable method of treatment :	Textile side of the fabric clean either dry with a soft brush or slightly wet cloth. The fabric should be left to dry at room temperature.			
In Drzovice 16.7.2024				

KINETIC s.r.o.

SNP 9/6 • 796 07 Držovice

tel.: +420 582 365 770-2

fax: +420 582 365 769

č.ú.. 377 886 323 / 0300

IČ: 277 28 234 • DIČ: CZ27728234



Ing. Hlahůlek Ivo

Jednatel společnosti Kinetic s.r.o.

