



KINETIC s.r.o  
 SNP 9/6  
 796 07 Držovice

+420 582 365 770 kinetic@kinetic.cz



## TECHNICAL DATA SHEET

<b>Name :</b>	<b>NYLON 70D/210T WR PU3000 RIPSTOP</b>		
<b>Supplier :</b>	KINETIC s.r.o. SNP 9/6 ; 796 07Držovice IČO:27728234 ; DIČ: CZ27728234 tel.: 582 365 770 email : kinetic@kinetic.cz		
<b>Manufactured :</b>	ROC		
<b>PROJECT</b>	<b>TESTING RESULTS</b>	<b>TESTING STANDARD</b>	<b>TOLERANCE</b>
<b>Description</b>	NYLON 70D/210T WR PU3000 RIPSTOP		
<b>Dyeing method:</b>	Piece dyeing		
<b>Textile :</b>	<u>100% polyester Ripstop</u>		
<b>Lamination :</b>	Polyuretan		
<b>Weight :</b>	95 g/m2	ISO 3801 (g/m2)	+/- 5%
<b>Dimensions :</b>	fabric width 58" - length 1 roll 50m		+/- 5%
<b>Tensile strength:</b>			
<b>warp</b>	646.55	ISO 13934-1 (N)	+/- 5%
<b>weft</b>	421.56	ISO 13937-2 (N)	+/- 5%
<b>Tear strength:</b>			
<b>warp</b>	23.52	ISO 13937-2 (N)	+/- 5%
<b>weft</b>	19.57		+/- 5%
<b>Water column :</b>	9400	ATCC-127 (mmH2O)	+/- 5%
<b>Abrasion resistance :</b>	> 90000	ISO 12947-2 (Cycles)	+/- 5%
<b>Others</b>	Certificate of compliance with the REACH regulation, confirming that the product meets the principles of the European Union directive REACH 1907/2006.		
<b>Laundry symbols :</b>	 DO NOT WASH DO NOT BLEACH DO NOT TUMBLE DRY DO NOT IRON DO NOT DRY CLEAN		
<b>Suitable method of treatment :</b>	Textile side of the fabric clean either dry with a soft brush or slightly wet cloth The fabric should be left to dry at room temperature		
<b>Recommended</b>	Recommended to store in a horizontal position, in a dry and well-ventilated area, away from sunlight and UV radiation		
	In Drzovice 15.4.2026		