



KINETIC s.r.o
 SNP 9/6
 796 07 Držovice
 +420 582 365 770 kinetic@kinetic.cz



TECHNICAL DATA SHEET

Name :	Nylon 200D/132T WR PVC REACH		
Supplier :	KINETIC s.r.o. SNP 9/6 ; 796 07Držovice IČO:27728234 ; DIČ: CZ27728234 tel.: 582 365 770 email : kinetic@kinetic.cz		
Manufactured :	Taiwan		
PROJECT	TESTING RESULTS	TESTING STANDARD	TOLERANCE
Description	NYLON 200D/132T PVC REACH		
Dyeing method:	Piece dyeing		
Textile :	<u>100% NYLON</u>		
Coating Type :	100% Virgin PVC		
Weight :	207,4 g/m2	ISO 3801 (g/m2)	+/- 5%
Dimensions :	fabric width 58" - length 1 roll 40m		+/- 5%
Tensile strength:	warp: 651.50	ISO 13934-1 (N)	+/- 5%
	weft: 482.13		+/- 5%
Tear strength:	weft: 19.72	ISO 13937-2 (N)	+/- 5%
	weft: 15.98		+/- 5%
Water column :	more than 20000	ATCC-127 (mmH2O)	+/- 5%
Adhesion of coating to fabric:	warp : 28.46	ASTM D751-19 (N)	
	weft : 28.18		
Abrasion resistance :	25 000	ISO 12947-2 (Cycles)	+/- 5%
Others	Certificate of compliance with the REACH regulation, confirming that the product meets the principles of the European Union directive REACH 1907/2006.		
Laundry symbols :	 DO NOT WASH DO NOT BLEACH DO NOT TUMBLE DRY DO NOT IRON DO NOT DRY CLEAN		
Suitable method of treatment :	Textile side of the fabric clean either dry with a soft brush or slightly wet cloth The fabric should be left to dry at room temperature		
Recommended	Recommended to store in a horizontal position, in a dry and well-ventilated area, away from sunlight and UV radiation		
In Drzovice 14.8.2024			