




KINETIC s.r.o
 SNP 9/6
 796 07 Držovice

+420 582 365 770 kinetic@kinetic.cz



TECHNICAL DATA SHEET

Name :	NYLON 70D/210T WR PU3000		
Supplier :	KINETIC s.r.o. SNP 9/6 ; 796 07Držovice IČO:27728234 ; DIČ: CZ27728234 tel.: 582 365 770 email : kinetic@kinetic.cz		
Manufactured :	ROC		
PROJECT	TESTING RESULTS	TESTING STANDARD	TOLERANCE
Description	NYLON 70D/210T WR PU3000		
Dyeing method:	Piece dyeing		
Textile :	<u>100% polyester Ripstop</u>		
Lamination :	Polyuretane		
Weight :	95 g/m2	ISO 3801 (g/m2)	+/- 5%
Dimensions :	fabric width 58" - length 1 roll 50m		+/- 5%
Tensile strength:			
warp	646.55	ISO 13934-1 (N)	+/- 5%
weft	421.56	ISO 13937-2 (N)	+/- 5%
Tear strength:			
warp	23.52	ISO 13937-2 (N)	+/- 5%
weft	19.57		+/- 5%
Water column :	9400	ATCC-127 (mmH2O)	+/- 5%
Abrasion resistance :	> 90000	ISO 12947-2 (Cycles)	+/- 5%
Others	Certificate of compliance with the REACH regulation, confirming that the product meets the principles of the European Union directive REACH 1907/2006.		
Laundry symbols :	 DO NOT WASH DO NOT BLEACH DO NOT TUMBLE DRY DO NOT IRON DO NOT DRY CLEAN		
Suitable method of treatment :	Textile side of the fabric clean either dry with a soft brush or slightly wet cloth The fabric should be left to dry at room temperature		
Recommended	Recommended to store in a horizontal position, in a dry and well-ventilated area, away from sunlight and UV radiation		
	In Drzovice 15.4.2026		