



KINETIC s.r.o
 SNP 9/6
 796 07 Držovice
 +420 582 365 770 kinetic@kinetic.cz



TECHNICAL DATA SHEET

| | | | |
|---------------------------------------|---|-------------------------|------------------|
| Name : | PES 500/300D/64T PVC | | |
| Supplier : | KINETIC s.r.o. SNP 9/6 ; 796 07Držovice IČO:27728234 ; DIČ: CZ27728234 tel.: 582 365 770 email : kinetic@kinetic.cz | | |
| Manufactured : | ROC | | |
| PROJECT | TESTING RESULTS | TESTING STANDART | TOLERANCE |
| Description | PES 500/300D/64T PVC | | |
| Dyeing method: | Piece dyeing | | |
| Textile : | <u>100% polyester</u> | | |
| Lamination : | PVC | | |
| Weight : | 389 | ISO 3801 (g/m2) | +/- 5% |
| Dimensions : | fabric width 58" - length 1 roll 40m | | +/- 5% |
| Tensile strength: | | | |
| warp | 1024.36 | ISO 13934-1 (N) | +/- 5% |
| weft | 690.37 | ISO 13937-2 (N) | +/- 5% |
| Tear strength: | | | |
| warp | 60.98 | ISO 13937-2 (N) | +/- 5% |
| weft | 46.40 | | +/- 5% |
| Water column : | 841 | ATCC-127 (mmH2O) | +/- 5% |
| Abrasion resistance : | 80 000 | ISO 12947-2 | +/- 5% |
| Others | | | |
| Laundry symbols : | DO NOT WASH DO NOT BLEACH DO NOT TUMBLE DRY DO NOT IRON DO NOT DRY CLEAN | | |
| Suitable method of treatment : | Textile side of the fabric clean either dry with a soft brush or slightly wet cloth The fabric should be left to dry at room temperature | | |
| Recommended | Recommended to store in a horizontal position, in a dry and well-ventilated area, away from sunlight and UV radiation | | |
| In Drzovice 14.4..26 | | | |