KINETIC s.r.o
SNP 9/6
796 07 Držovice
+420 582 365 770 kinetic@kinetic.cz

TECHNICAL DATA SHEET

Name:	**KORTEXIN 600D/64T C0 WR PVC REACH UV**		
Supplier:	KINETIC s.r.o. SNP 9/6; 796 07 Držovice IČO: 27728234; DIČ: CZ27728234 tel.: +20 739 031 103 email: kinetic@kinetic.cz		
Manufactured:	ROC		
PROJECT	TESTING RESULTS	TESTING STANDARD	TOLERANCE
Description	KORTEXIN 600D/64T C0 WR PVC REACH UV		
Dyeing method:	Sollution dyeing		
Textile:	100% polyester		
Coating type:	100% Virgin PVC		
Finishing:	C0-WR PFAS-free (Fluorocarbon-free)		
Weight:	439	ISO 3801 (g/m²)	+/- 5%
Dimensions:	fabric width 58" - lenghth 1 roll 40m		+/- 5%
Tensile strength:			
warp	1417.74	ISO 13934-1 (N)	+/- 5%
weft	1317.49	ISO 13934-1 (N)	+/- 5%
Tear strength:			
warp	79.83	ISO 13937-2 (N)	+/- 5%
weft	77.15	ISO 13937-2 (N)	+/- 5%
Abrasion resistance:	＞90000	ISO 12947-2	+/- 5%
Water column:	3290	EN 20811 (mmH_2O)	+/- 5%
Others	Certificate of compliance with the REACH regulation, confirming that the product meets the principles of the European Union directive REACH 1907/2006.		
	PFAS-free (C0): The water-repellent finish (DWR) is completely free of per- and polyfluoroalkyl substances (PFAS/PFC), ensuring full environmental compliance with		
	OEKO-TEX® STANDARD 100 **Certifikate:** PG015 281880		
Laundry symbols:	 DO NOT WASH DO NOT BLEACH DO NOT TUMBLE DRY DO NOT IRON DO NOT DRY CLEAN		
Suitable method of treatment:	Textile side of the fabric clean either dry with a soft brush or slightly wet cloth The fabric should be left to dry at room temperature		
Recommended	Recommended to store in a horizontal position, in a dry and well-ventilated area, away from sunlight and UV radiation		
	In Drzovice 14.10.2026		