KINETIC s.r.o
SNP 9/6
796 07 Držovice
+420 582 365 770 kinetic@kinetic.cz

TECHNICAL DATA SHEET

Name :	**KORTEXIN SLIM 600D/62T RIPSTOP WR REACH**		
Supplier :	KINETIC s.r.o. SNP 9/6 ; 796 07Držovice IČO:27728234 ; DIČ: CZ27728234 tel.: 582 365 770 email : kinetic@kinetic.cz		
Manufactured :	ROC		
PROJECT	TESTING RESULTS	TESTING STANDARD	TOLERANCE
Description	KORTEXIN SLIM 600D/62T RIPSTOP WR REACH		
Dyeing method:	Piece dyeing		
Textile :	100% polyester		
Lamination :	Polyuretan		
Weight :	250	ISO 3801 (g/m²)	+/- 5%
Dimensions :	fabric width 58" - lenghth 1 roll 50m		+/- 5%
Tensile strength:			
warp	1830.05	ISO 13934-1 (N)	+/- 5%
weft	1448.85	ISO 13937-2 (N)	+/- 5%
Tear strength:			
warp	138.66	ISO 13937-2 (N)	+/- 5%
weft	138.68		+/- 5%
Abrasion resistance :	80000	ISO 12947-2	+/- 5%
Water column :	>10000	ATCC-127 (mmH_2O)	+/- 5%
Others	Certificate of compliance with the REACH regulation, confirming that the product meets the principles of the European Union directive REACH 1907/2006. OEKO-TEX® STANDARD 100 **Číslo certifikátu:** PG015 281880		
Laundry symbols :	 DO NOT WASH  DO NOT BLEACH  DO NOT TUMBLE DRY  DO NOT IRON  DO NOT DRY CLEAN		
Suitable method of treatment :	Textile side of the fabric clean either dry with a soft brush or slightly wet cloth The fabric should be left to dry at room temperature		
Recommended	Recommended to store in a horizontal position, in a dry and well-ventilated area, away from sunlight and UV radiation		
	In Drzovice 15.4.2026		